

MODEL		MPPT 60A		MPPT 80A	
Nominal Battery System Voltage		12V/24V/48VDC (Auto detection) ; 36V(setting)			
CONTROLLER INPUT	Battery Voltage	12V	24V	36V	48V
	Maximum Solar Input Voltage	100V	145V		
	PV Array MPPT Voltage Range	15~95V	30~130V	45~130V	60~130V
	Max PV Input Power(12V)	938W		1250W	
	Max PV Input Power(24V)	1875W		2500W	
	Max PV Input Power(36V)	2813W		3750W	
	Max PV Input Power(48V)	3750W		5000W	
BATTERY & CHARGER	Charging Set points	Absorption Stage		Float Stage	
	Flooded Battery	14.2V/28.4V/42.6V/56.8V		13.7V/27.4V/41.1V/54.8V	
	AGM/Gel/LEAD battery (Default)	14.4V/28.8V/43.2V/57.6V		13.7V/27.4V/41.1V/54.8V	
	Over-charging voltage	15.5V/30.0V/45.0V/60.0V			
	Over-charging comeback voltage	14.5V/29.5V/44.5V/59.0V			
	Battery defect voltage	10.0V/17.0V/25.5V/34.0V			
	Temperature Compensation coefficient	-5mv/°C /cell (25°C vef)			
	Peak Conversion efficiency	98% (MPPT Efficiency 99%)			
	Max Charging Current	60 amps continuous @ 40°C ambient		80 amps continuous @ 40°C ambient	
GENERAL SPECIFICATION	Radiating mode	Fan cooling			
DISPLAY & PROTECTION	Protections	Solar high voltage disconnect Solar high voltage reconnect Battery high voltage disconnect Battery high voltage reconnect High temperature disconnect High temperature reconnect			
MECHANICAL SPECIFICATIONS	Mounting	Wall mount			
	Machine Dimension(W×H×D)	152×100×294mm (per pcs)			
	G.W(Kg)	3Kg/pcs			
	Package Dimension(W×H×D)	612×308.2×235.6mm (5pcs/Carton)			
	Gross Weight(Kg)	17.4Kg (per Carton)		19Kg (per Carton)	
OTHER	Environmental Rating	Indoor			
	Operation Temperature Range	-25~55°C			
	Ambient humidity	0~90% relative humidity(non-condensing)			
	Altitude	≤3000m			
	Loading(20GP/40GP/40HQ)	3000pcs / 6000pcs / 7200pcs			