## **ISolar SML 3K Plus MPPT Solar Inverter**



- Pure sine wave inverter
- Built-in MPPT solar charge controller
  Selectable input voltage range and frequency according to city power in your country
- Charging current is setable according to your battery type
  Configurable AC/Solar input priority via LCD setting
  Compatible to mains voltage or generator power

- Auto restart while AC is recovering
  Overload and short circuit protection
- Smart charging system optimizes battery performance
  Cold start function
- Parallelable up to 6 units which available on 4K/5K only

## 230Vac MPPT Solar Inverter Specification

Model	ISolar SML 3K 24V PLUS
Rated power	3000VA
	2400W
INPUT	
Voltage	230VAC
Slectable Voltage Range	170-280 VAC (For Personal Computers)
	90-280 VAC (For Home Applicances)
Frequency Range	50Hz/60Hz (Auto Sensing)
OUTPUT	
AC Voltage Regulation(Batt. Mode)	230VAC±5%
Surge Power	6000VA
Efficiency(Peak)	
Transfer Time	10ms (For Personal Computer
	20ms (For Home Applicances)
Waveform	Pure sine wave
BATTERY&AC CHARGER	
Battery voltage	24VDC
Floating Charge Voltage	27VDC
Overcharge Protection	31VDC
Maximum Charge Current	20A or 30A
Maximum PV Array Power	1500W
MPPT Range@Operating Voltage	30VDC~115VDC
Maximum PV Array Open Circut Voltage	145VDC
Maximum Charging Current	60A
Maximum Efficiency	98%
Standby Power Consumption	2W
PHYSICAL	
Dimension,D*W*H(mm)	128*272*355
Net Weight(kgs)	11.5

<sup>\*</sup> Product specifications are subject to change without further notice