



# RESACS - 600W

## Features

- Module-level MPPT, 5~25% more power generation
- 25-year use life, same as PV module
- For PV power plants in operation and under construction
- Easy to install



# Model

# Resacs - 600W

DC input	
Max input power	600W
Operation voltage range	7 ~ 60V
MPPT voltage range	7 ~ 60V
Max input current	16A
Over-current protection	18A
Over-temperature protection	150 °C
DC output	
Max output current	16A
Output voltage limit	42V
Max system voltage	1500V
72-cell module in serial @1500V	36 pcs
72-cell module in serial @1100V	26 pcs
72-cell module in serial @1000V	24 pcs
Efficiency	
Peak efficiency	99.5%
Power loss @5A	0.9W
Power loss @8A	1.4W
Power loss @12A	2.9W
Power loss @15A	4.5W
Power loss @20A	7.2W
General data	
Dimensions ( L×W×H )	103×105.3×21.3mm
Weight	0.65Kg
input/output cable length	150/1050mm
input/output cable size	4mm <sup>2</sup> (12AWG) / 4mm <sup>2</sup> (12AWG)
Terminals	MC4(compatible)
Environmental Protection Rating	IP67/NEMA6
Relative humidity	0~100%RH
Operating temperature range	-40~+65°C
Cooling	Natural cooling