

TS-EVC11-003

Product overview

Smart charger, Small size, Stylish design

Easy control via mobile APP, always being the most reliable and safe home charger.



Specification	Model	TS-EVC07-003	TS-EVC11-003	TS-EVC22-003
Electrical Properties	Voltage	230V AC ±10%	380V AC ±10%	380V AC ±10%
	Output Current	32A	16A	32A
	Frequency	50/60Hz	50/60Hz	50/60Hz
	Output Power	7kw	11kw	22kw
	Residual current protection	TYPE A (AC 30MA)		
Design	Charging Outlet	4M charging cable with type1/2 plug or type2 socket		
	Housing Material	PCV0 for outdoor		
	Installation Method	Wall-mount/Floor-stand		
	Communication Protocol	OCPP 1.6 J-SON		
	Safety Standard	EN 61851-1		
	Warranty	2 years		
Environmental Performance	Protection Level	IP65		
	Temperature/Humidity	-30~50°C/5%~95% without condensation		
	Working Altitude	< 2000M		
	Application Site	Indoor/Outdoor		
	Working temperature	-30 C ~ 60 C		
	Storage temperature	-40 C ~ 70 C		
	Working humidity	5%~95%, No condensation		
	Altitude	≤2000m		
	Salt spray test	Meet IEC 61851-1: 2017		
	Atmospheric pressure	80kPa~ 101kPa		
	Temperature and humidity cycle	Meet IEC 61851-1: 2017		
Functionality	Network Gateway	Bluetooth and WIFI as default		
	Mobile APP (ios and Android supported) functions under Bluetooth	Scheduled charging · Start charging· Stop charging· Current adjustment (memorable)· plug and play charging switch on APP· Charging status shown on APP		
	Added APP functions under WIFI / 4G	Charging records shown on mobile APP· view and update the PIN code· firmware updating function(OTA)· multiple wallbox control		
Packing Details	Product Size	228.5*228.5*100mm	228.5*228.5*100mm	228.5*228.5*100mm
	Product Weight	4.4KG	5.2KG	5.4KG
Optional Config	Residual current protection	TYPE B (AC 30MA + DC 6 MA) as optional		
	Network Gateway	4G as optional		
	O-PEN detection	as optional		
	RFID	as optional (with 3 RFID cards)		
	load balance	RS485 meter as optional		